This drawing is the sole property of Miether Bearing Products and contains confidential and proprietary It is being provided to you for your use and may not be disclosed to any third party or used for any other purpose without Miether's prior written consent. The [materials] must be returned to the Company upon its demand. Your acceptance of these materials constitutes your acceptance of the foregoing terms. C-14574 FOR Ø14 BASE BOLTS (4) CORED HOLES - 20 -1 MIE 215 198 WIDTH WAS 98 RWB per KAB 7-30-04 REDRAWN FOR CONFORMITY RWB per KAB Ξ 7-26-04 REVISIONS DRILLED & TAPPED FOR §-16 NC EYEBOLT MICRO-INCH VALUE SYMBOL A.I.S.I. **⋄** 16 4 32 63 125 250 500 1000 \$ \$ \$ \$ 7.063 7.053 FINISHES ISE SPECIFIED

ES +- 0" 30'
" +- 1/16" ***** ITEM STATIC OIL LEVEL 10 6 O ω N 9 8 4 ~ LOCKWASHER TRIPLE SEAL STABILIZING RING SR-34-0 SPHERICAL ROLLER BEARING PIPE PLUG CAP BOLT HEX. DOWEL TRIPLE LOCKWASHER LOCKNUT HOUSING Ř ALCO INDUSTRIES COMPANY ODESSA, TX. DESCRIPTION SEAL SDAF 534 05-15 RING RING HEAD USA AN-34 W - 34LER-LER-148 ℗ -161 60 8-18 NPT A-10586 C-15208-R ø₂ x 1" LONG A-10673 B-10421 A-10609 22234/W-33 00251 18 SPLIT MED. 18-7 NC x 72 LONG DETAIL ASSEMBLY DRAWING 6 FIXED FLOAT ø616 07-07 x 06-07 DRAWING NO. C-14574 ASSEMBLY NO. PXD. FLT. 4 N