

### 222 K Bearing Series

Bearing Size	Shaft Dia. (d1)in.	Designations				Mass lbs.	Dimensions			
		Complete Adapter	Lock-nut	Lock-washer	Sleeve		L	F	(d2)Pitch Diameter	Threads Per Inch
22213 K	2 3/16	SNW 13	N 13	W 13	S 13	1.40	2.094	0.792	2.508	18
22214 K	2 5/16	SNW 14	N 14	W 14	S 14	1.80	2.172	0.792	2.711	18
22215 K	2 7/16	SNW 15	AN 15	W 15	S 15	2.30	2.297	0.895	2.875	12
22216 K	2 11/16	SNW 16	AN16	W 16	S 16	2.25	2.376	0.895	3.082	12
22217 K	2 15/16	SNW 17	AN 17	W 17	S 17	2.40	2.486	0.926	3.285	12
22218 K	3 3/16	SNW 18	AN 18	W 18	S 18	2.65	2.646	1.010	3.472	12
22219 K	3 1/4	SNW 19	AN 19	W 19	S 19	4.10	2.760	1.041	3.671	12
22220 K	3 7/16	SNW 20	AN 20	W 20	S 20	4.25	2.869	1.073	3.863	12
22222 K	3 15/16	SNW 22	AN 22	W 22	S 22	4.65	3.206	1.135	4.290	12
22224 K	4 3/16	SNW 24	AN 24	W 24	S 24	6.25	3.466	1.166	4.660	12
22226 K	4 7/16	SNW 26	AN 26	W 26	S 26	8.70	3.762	1.229	5.050	12
22228 K	4 15/16	SNW 28	AN 28	W 28	S 28	9.05	3.981	1.291	5.441	12
22230 K	5 3/16	SNW 30	AN 30	W 30	S 30	12.20	4.241	1.354	5.832	12
22232 K	5 7/16	SNW 32	AN 32	W 32	S 32	15.30	4.578	1.510	6.200	8
22234 K	5 15/16	SNW 34	AN 34	W 34	S 34	16.77	4.847	1.541	6.575	8
22236 K	6 7/16	SNW 36	AN 36	W 36	S 36	16.96	5.038	1.573	6.982	8
22238 K	6 15/16	SNW 38	AN 38	W 38	S 38	17.53	5.261	1.604	7.388	8
22240 K	7 3/16	SNW 40	AN 40	W 40	S 40	21.30	5.484	1.666	7.763	8
22244 K	7 15/16	SNW 44	N 44	W 44	S 44	27.60	5.901	1.698	8.544	8

